C1, C1 200

| C1, C1     |                  | Model code: 0191  |                 |                  |         |
|------------|------------------|-------------------|-----------------|------------------|---------|
|            | Tyre type, front | Size, front       | Tyre type, rear | Size, rear       | Comment |
|            | Bridgestone      |                   |                 |                  |         |
|            | Hoop B 03        | 120/70-13 M/C 53P | Ноор В 02       | 140/70-12 65L TL |         |
|            |                  |                   |                 |                  |         |
| C1 200, C1 |                  | Model code: 0192  |                 |                  |         |

Tyre type, front Size, front Tyre type, rear Size, rear Comment

Bridgestone

Hoop B 03 120/70-13 M/C 53P Hoop B 02 140/70-12 65L TL

## Legend

| No. | Description   |
|-----|---|
|     |   |
| 2   | if not included in listing on registration document have tyre pair entered by technical inspectorate.   |
| 3   | if not included in listing on registration document have tyre pair entered by technical inspectorate or keep certificate with the vehicle at all times. |
| 4   | The maximum permissible top speed of 160 km/h must be stated where it is clearly noticeable in the rider's field of vision (e.g. sticker).              |

| 5  | The maximum permissible top speed of 130 km/h must be stated where it is clearly noticeable in the rider's field of vision (e.g. sticker). |
|----|--|
| 6  | Mount spoke wheels only with hose.   |
| 7  | Rear-wheel rim 5.00x17   |
| 8  | Rear-wheel rim 5.50x17   |
| 9  | Cast wheels, rims MTH2<br>3.50x17E and MTH2 4.50x18E   |
| 11 | Approved for special vehicles only.  |
| 12 | Tubeless.  |
| 13 | Not permissible for special vehicles.  |
| 15 | The maximum permissible top speed of 170 km/h must be stated where it is clearly noticeable in the rider's field of vision (e.g. sticker). |
| 16 | Approved only without ABS.   |
| 17 | Rear-wheel rim 6.00x17   |

| 18 | Clearance certificate must be obtained from the tyre manufacturer.   |
|----|--|
| 19 | Spoked wheels, rims MTH2 1.85x21 and MTH2 2.50x17  |
| 20 | Spoked wheels, rims MTH2 3.50x17 and MTH2 4.00x17  |
| 21 | Fit the front tyre with tube, because the rim is not suitable for tubeless tyres.  |
| 22 | Tyre not in production at this time.   |
| 23 | Rear-wheel rim 2.75x18   |
| 24 | Rear-wheel rim 3.00x17   |
| 25 | Approved for cast wheels.  |
| 27 | Operation permissible only without spray guard fitted (see on-board documentation for instructions on removal and installation). |
| 28 | Recommended for OE forged wheel  |

| 29 | Not for forged wheel OE  |
|----|--|
| 30 | If the rear wheel tyre size is changed from 190/55 ZR 17 to 200/55 ZR 17 or vice versa, the parameters of the control systems have to be re-coded; BMW Motorrad recommends having this work done by an authorised BMW Motorrad dealer. |
| 31 | Not approved for spoke rims.   |
| 32 | The maximum permissible top speed of 190 km/h must be stated where it is clearly noticeable in the rider's field of vision (e.g. sticker).   |
| 33 | National-market version for China  |
| 34 | National-market version for Brazil   |
| 35 | Recommended for OE carbon wheel  |